

Package: shinycroneditor (via r-universe)

November 23, 2024

Title 'shiny' Cron Expression Input Widget

Version 1.0.0

Description A widget for 'shiny' apps to handle schedule expression input, using the 'cron-expression-input' JavaScript component.

Note that this does not edit the 'crontab' file, it is just an input element for the schedules. See

<https://github.com/DatalabFabriek/shinycroneditor/blob/main/inst/examples/shiny-app.R>

for an example implementation.

Imports htmltools, htmlwidgets

Suggests shiny

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.1

NeedsCompilation no

Author Harmen van der Veer [aut, cre]

Maintainer Harmen van der Veer <harmen@datalab.nl>

Date/Publication 2024-09-23 13:00:06 UTC

Config/pak/sysreqs make

Repository https://semipublicdlf.r-universe.dev

RemoteUrl https://github.com/cran/shinycroneditor

RemoteRef HEAD

RemoteSha 810e0159ad08c0699d715279ab110807fcd99a51

Contents

cron	2
croneditor-shiny	3

Index	5
--------------	----------

cron	<i>Cron editor, creates a 'htmlwidgets' object, for use in a 'shiny' dashboard</i>
------	--

Description

Cron editor, creates a 'htmlwidgets' object, for use in a 'shiny' dashboard

Usage

```
cron(schedule, width = NULL, height = NULL, elementId = NULL)
```

Arguments

schedule	Any valid cron schedule, for example "0 6 * * *"
width	How wide should the editor be? Defaults to NULL, meaning 100%
height	How high should the editor be? Defaults to NULL, meaning 32px
elementId	Optionally specify the ID of the element

Value

Returns a 'htmlwidgets' object that can be used in a 'shiny' app

Examples

```
# A simple cron editor in a Shiny app
if (interactive()) {
  library(shiny)
  library(shinycroneditor)

  ui <- fluidPage(
    titlePanel("Cron Expression Input Widget"),
    mainPanel(
      shinycroneditor::cronOutput("cronschedule1",
        label = "Choose your first schedule",
        language = "en-US"),

      shiny::div(
        "Your first chosen schedule is: ",
        verbatimTextOutput("cronExpression1")
      ),

      shinycroneditor::cronOutput("cronschedule2",
        label = "Choose your second schedule",
        language = "en-US"),

      shiny::div(
        "Your chosen second schedule is: ",
```

```

        verbatimTextOutput("cronExpression2")
      )
    )
  )

  server <- function(input, output, session) {

    output$cronschedule1 <- shinycroneditor::renderCron({
      shinycroneditor::cron("0 6 * * *")
    })

    output$cronExpression1 <- renderPrint({
      input$cronschedule1
    })

    output$cronschedule2 <- shinycroneditor::renderCron({
      shinycroneditor::cron("30 1,3,7 * * *")
    })

    output$cronExpression2 <- renderPrint({
      input$cronschedule2
    })

  }

  shinyApp(ui, server)
}

```

 croneditor-shiny

Shiny bindings for cron editor

Description

Output and render functions for using cron editor within 'shiny' applications and interactive 'markdown' documents.

Usage

```

cronOutput(
  outputId,
  label = NULL,
  language = "en-US",
  width = "100%",
  height = NULL
)

renderCron(expr, env = parent.frame(), quoted = FALSE)

```

Arguments

outputId	output variable to read from
label	The label to show, just like in a regular Shiny input element. Set to NULL if you don't want a label.
language	The language the cron editor's UI will be in. Choose one of en-US, nl-NL, es-ES, zh-CN. Note that if you have multiple cron editors on one page, the last editor's language will be the one for all editors.
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a test
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

Value

An 'htmlwidgets' object for use in a shiny app, containing a placeholder for where the cron input element is rendered.

A 'htmlwidgets' object for use in a 'shiny' app as an input element

Index

`cron`, [2](#)

`croneditor-shiny`, [3](#)

`cronOutput` (`croneditor-shiny`), [3](#)

`renderCron` (`croneditor-shiny`), [3](#)